



PEXOL ATF MV

Product Description and Field of Use

This is a full synthetic lubricant based on carefully selected very high quality base oils, which meets the requirements of the General Motors Dexron VI specification. Its special composition allows it to be used in all applications, where the older Dexron II and Dexron III fluids are recommended.

Properties and Benefits

- Friction properties, very smooth shifting, no vibration.
- Wear protection, significantly extended transmission life.
- Extended oil life, excellent thermal and oxidation stability.

Specifications and Approvals Fulfilled

Dexron VI, Mercon LV, Aisin Warner JWS 3309/3324 (WS), Chrysler Dodge Mopar AS68RC (Type IV), Chrysler Dodge Mopar ATF+/+2/+3/+4, Ford Mercon /WSS-M2C138-CJ/166-H/922-A1/924-A, Honda Acura DW-1/ATF-Z1 (за исключением CVT), Hyundai/Kia SP-II/SP-III/SP-IV/SP-IV M/SP-IV RR, Hyundai/Kia JWS3314/9683, Isuzi Besco ATF II/III, Nissan Matic C/D/J/K/S, Jaguar ATF 3403 M115/JLM 20238, JASO M315-2013 1A/1A-LV/2A, Mazda ATF M-III/M-V, Mitsubishi SK/SP-II/SP-III/SP-IV/AW/J2/J3/ATF PA, Subaru ATF/ATF 5AT/ATF HP, Suzuki ATF 3309/3314/3317/2326/2384 K, Toyota D-II/D-III/T-III/T-IV/WS

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm ³	ASTM 4052	0.847
K. Viscosity, @ 100°C	cSt	ASTM D 445	6,0
Viscosity Index		ASTM D 2270	151
Flashing Point	°C	ASTM D 92	210
Pour Point	°C	ASTM D 97	-40

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.