

PEXOL P5 5W-30 C3

Product Description and Field of Use

It is a fully synthetic engine oil that is compatible with the exhaust emission systems of gasoline, passenger diesel and light commercial vehicles, especially those with diesel particulate filter (DPF) and meeting the requirements of Euro 4 and 5 emission standards.

Properties and Benefits

- Provides unique protection against wear and corrosion thanks to the high-tech synthetic base oils and high-performance additives it contains.
- With its superior technology, it increases engine performance and provides fuel economy by reducing friction at all temperatures.
- Provides excellent protection against rust and wear in the engine.
- Thanks to its high viscosity index, it creates a durable oil film in the engine at all temperatures, ensuring minimum wear in the engine.
- It prevents sediment accumulation and increases the performance of the engine by dispersing the particles formed as a result of combustion in the environment with the help of detergent-dispersant additives in its content.

Specifications and Approvals Fulfilled

API SN/SN Plus, ACEA C3, BMW Longlife-04, MB 229.31/229.51/229.52, Opel Ov040154701, VW 505.00/505.01

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm ³	ASTM 4052	0.861
K. Viscosity, @ 100°C	cSt	ASTM D 445	9.3-12.5
Viscosity Index		ASTM D 2270	160
CCS-30°C	mPa s	ASTM D 5293	Max.6600
Flashing Point	°C	ASTM D 92	212
Pour Point	°C	ASTM D 97	-38

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.